



火焰坡口切割装置

*oxy-fuel*

*bevel cutting units*

**MESSER**   
Cutting Systems

## 火焰坡口切割装置

### 三割炬坡口切割装置 N, 可旋转

- 纵横向 V, X, Y 与 K 形坡口切割
- 手动角度调整 30° - 45°
- 带宽 50 - 130 mm (最大 260 mm)

### 三割炬坡口切割装置 KN, 可旋转

- (说明略)
- 与 不带自动回旋转的 D/KS 同

### 三割炬坡口切割装置 D/KS

- 无限自动旋转
- 用于 V, X, Y 与 K 形坡口切割
- 坡口切割可达 80mm 厚
- 直切可达 150mm 厚
- 手动调整角度范围 15° - 60°
- 横向调整 ± 50 mm
- 行程 250 mm

### 三割炬坡口切割装置 D/AFL

- 无限自动旋转
- 用于 V-, X-, Y- 和 K 轴的切割
- 坡口切割可达 80mm 厚
- 直切可达 150mm 厚
- 手动或数控调整角度范围 15° - 60°
- 行程 250 mm

## oxy-fuel bevel cutting units

### Triple Bevel head n, swivelling

- V, X, Y and K cuts in longitudinal and transverse machine directions
- Manual angle adjustment 30° - 45°
- Strip widths 50 - 130 mm (max. 260 mm)

### Triple bevel head KN, swivelling (no illustration)

- As D/KS without auto-rotation

### Triple bevel head D/KS

- Automatic infinitely rotating
- For V, X, Y and K cuts
- Bevel cuts up to 80 mm plate thickness
- Straight cuts up to 150 mm plate thickness
- Angle adjustment manual 15° - 60°
- Lateral adjustment ± 50 mm
- Stroke 250 mm

### Triple bevel head D/AFL

- Automatic infinitely rotating
- For V, X, Y and K cuts
- Bevel cuts up to 80 mm plate thickness
- Straight cuts up to 150 mm plate thickness
- Angle adjustment motorised, CNC or manual 15° - 60°
- Angle adjustment motorised with the CNC 15° - 60°
- Stroke 250 mm



三割炬坡口切割装置 N  
Triple bevel head N



三割炬 坡口切割装置 D/KS  
Triple bevel head D/KS



三割炬坡口切割装置 D/AFL  
Triple bevel head D/AFL

梅塞尔切割焊接（中国）有限公司  
江苏省昆山市南浜路 528 号  
电话: +86 (0) 512 57314949  
400 800 6986  
传真: +86 (0)512 57395052  
www.messer-cs.cn

Messer Cutting Systems (China)Ltd.  
528 Nangbang Road  
Kunshan, Jiangsu  
P.R. China  
Tel. +86 (0) 512 57314949  
Fax +86 (0)512 57395052  
www.messer-cs.cn